

Aquaslab Permeable Block Paving


Data Sheet




Specially designed incorporating a slot and chamfer which allows water to permeate through the finished surface at a high rate. Available in a wide range of colours and finishes, Aquaslab offers an aesthetic appearance for all environments. Full ancillary kerb system to complement the range is also available. Recommended lay - staggered stretcher bond.

Colours


For an accurate colour match please request a sample.




Natural




Charcoal




Burnt Red *



Red Brindle



Golden Brindle *



Purbeck * †

Specification

Plan size (mm)	Thickness (mm)	Area per pack (m ²)	Blocks per pack	Pack weight (tonne)
450 x 300	60	11.34	84	1.49
Precast concrete block paving Manufactured to: BS EN 1339:2003 Tensile splitting strength 3.5 Mpa	Strength durability Class 1 Slip/skid resistance Satisfactory		Finishes Standard finish Bush hammered finish †	Applications Non-trafficked pedestrian areas/occasional traffic overrun

The Aquaslab permeable block is best used in combination with the Formpave Aquaflow System, a unique patent protected sub base design which utilises geogrids to reduce sub base depth without effecting structural strength. This system has BBA Accreditation and we offer a free bespoke design service to help you minimise your construction costs. Although every effort is made to ensure consistency of product colour, variations between production batches can occur. Formpave recommend that all products are thoroughly mixed on site by drawing from a minimum of three packs. † Special order * Colour purposes only