

Ecogranite Aquaflow Permeable Block Paving

Data Sheet




a Forterra brand



With a striking bush hammered finish, exposing sparkling granite and provides an excellent skid / slip resistance. Specially designed incorporating a slot and chamfer, allowing water to permeate through the finished surface at a high rate. Recommended lay - 45° or 90° herringbone for all trafficked areas. The Ecogranite Aquaflow block can be specified for all sites designed under BS7533-Pt13. Full ancillary kerb system to complement range is also available.

Colours

For an accurate colour match please request a sample.



Cornish Silver Grey



Balmoral



Tintagel *



Victoria * †



Truro * †



Braemar * †



Lochnagar *

UP TO 77%
BY-PRODUCT
MATERIAL



One of the most sustainable paving options currently available.



Specification

Plan size (mm)	Thickness (mm)	Area per pack (m ²)	Blocks per pack	Pack weight (tonne)	
200 x 100	60	11.2	560	1.47	
200 x 100	80	8.0	400	1.41	
Precast concrete block paving Manufactured to: BS EN 1338:2003 Tensile splitting strength 3.6 Mpa BBA certificate: 97/3373		Abrasion 60mm block Class 3 Abrasion 80mm block Class 4 Resistance to weathering Class 3 Slip/skid resistance Extremely low		Finishes Bush hammered finish	Applications Residential and commercial projects, including driveways, access roads and car parks.

The Ecogranite Aquaflow permeable block is best used in combination with the Formpave Aquaflow System, a unique patent protected sub base design which utilises geogrids to reduce sub base depth without effecting structural strength. This system has BBA Accreditation and we offer a free bespoke design service to help you minimise your construction costs. Although every effort is made to ensure consistency of product colour, variations between production batches can occur. Formpave recommend that all products are thoroughly mixed on site by drawing from a minimum of three packs. † Special order * Colour purposes only