

# Ecogranite Aquasett Permeable Block Paving

## Data Sheet




a Forterra brand




With a striking bush hammered finish, exposing sparkling granite and provides an excellent skid / slip resistance. Specially designed, incorporating a slot and chamfer which allows water to permeate through the finished surface at a high rate. Available in mixed packs or large block only. Can be specified for all sites designed under BS7533-Pt13. Full ancillary kerb system to complement the range is also available. Recommended lay: Combined pack - staggered stretcher bond. Large blocks - herringbone.

### Colours

For an accurate colour match please request a sample.



Cornish Silver Grey



Balmoral †



Tintagel †



Victoria †



Truro \* †



Braemar \* †



Lochnagar \* †

**UP TO 77%  
BY-PRODUCT  
MATERIAL**



One of the most sustainable paving options currently available.

### Specification

| Combined Packs  |                | 60mm (Depth)   | 80mm (Depth)                            |   |  |
|---|----------------|--|---|---|--|
| Total quantity of mixed blocks per pack   |                | 434  | 310                                     |   |  |
| Qty of Blocks   | 250 x 150mm    | 140  | 100                                     |   |  |
| Per Pack  | 150 x 150mm    | 196  | 140                                     |   |  |
| (Ind blocks/sizes)  | 100 x 150mm    | 98   | 70                                      |   |  |
| Area per pack (m <sup>2</sup> )   |                | 11.2   | 8.0                                     |   |  |
| Weight per pack (tonne)   |                | 1.47   | 1.42                                    |   |  |
| Plan size (mm)  | Thickness (mm) | Area per pack (m <sup>2</sup> )  | Blocks per pack                         | Pack weight (tonne)   |  |
| 250 x 150   | 60             | 10.5   | 280                                     | 1.38  |  |
| 250 x 150   | 80             | 7.5  | 200                                     | 1.33  |  |
| Precast concrete block paving<br>Manufactured to: BS EN 1338:2003<br>Tensile splitting strength 3.6 Mpa |                | Abrasion 60mm block Class 3<br>Abrasion 80mm block Class 4<br>Resistance to weathering Class 3<br>Slip/skid resistance Extremely low | <b>Finishes</b><br>Bush hammered finish | <b>Applications</b><br>Residential and commercial projects including driveways, access roads and carparks |  |

The Ecogranite Aquasett permeable blocks are best used in combination with the Formpave Aquaflow System, a unique patent protected sub base design which utilises geogrids to reduce sub base depth without effecting structural strength. This system has BBA Accreditation and we offer a free bespoke design service to help you minimise your construction costs. Although every effort is made to ensure consistency of product colour, variations between production batches can occur. Formpave recommend that all products are thoroughly mixed on site by drawing from a minimum of three packs. † Special order \* Colour purposes only

**Formpave**

Tufthorn Avenue, Coleford  
Gloucestershire, GL16 8PR

**Tel:** 01594 836 999  
**Fax:** 01594 810 577

**Email:** sales@formpave.co.uk  
**Web:** www.formpave.co.uk

