

Ecogranite Aquaslab Permeable Block Paving

Data Sheet



a Forterra brand



With a striking bush hammered finish, exposing sparkling granite and provides an excellent skid / slip resistance. Specially designed, incorporating a slot and chamfer which allows water to permeate through the finished surface at a high rate. Recommended lay - staggered stretcher bond. The Ecogranite Aquaslab can be specified for all sites designed under BS7533-Pt13. Full ancillary kerb system to complement the range is also available.

Colours

For an accurate colour match please request a sample.



Cornish Silver Grey *



Balmoral †



Tintagel * †



Victoria * †



Truro †



Braemar †



Lochnagar * †

**UP TO 77%
BY-PRODUCT
MATERIAL**



One of the most sustainable paving options currently available.

Specification

| Plan size (mm) | Thickness (mm) | Area per pack (m ²) | Blocks per pack | Pack weight (tonne) |
|---|---|---------------------------------|---|---|
| 450 x 300 | 60 | 11.34 | 84 | 1.49 |
| Precast concrete block paving Manufactured to: BS EN 1339:2003 Tensile splitting strength 3.6 Mpa | Strength durability Class 1 Slip/skid resistance Extremely low | | Finishes Bush hammered finish | Applications Non-trafficked pedestrian areas/occasional traffic overrun |

The Ecogranite Aquaslab permeable block is best used in combination with the Formpave Aquaflow System, a unique patent protected sub base design which utilises geogrids to reduce sub base depth without effecting structural strength. This system has BBA Accreditation and we offer a free bespoke design service to help you minimise your construction costs. Although every effort is made to ensure consistency of product colour, variations between production batches can occur. Formpave recommend that all products are thoroughly mixed on site by drawing from a minimum of three packs. † Special order * Colour purposes only