

Ecogranite Cobbles Block Paving

Data Sheet



a Forterra brand




Specifically designed for use in projects where architectural heritage is a major consideration. Created to emulate the old stone, traditionally used in rural and heritage sites. Can be traditionally coursed or laid in a more unusual pattern such as circles or Flanders fans. The bush hammered finish provides an excellent slip/skid resistance. Ecogranite kerb systems, edging and starter circles have been specially designed to complement the range.

Colours

For an accurate colour match please request a sample.



Cornish Silver Grey



Balmoral



Tintage! *




Victoria †



Truro * †



Braemar * †



Lochnagar * †

**UP TO 77%
BY-PRODUCT
MATERIAL**



One of the most sustainable paving options currently available.

Specification

Plan size (mm)	Thickness (mm)	Area per pack (m ²)	Blocks per pack	Pack weight (tonne)
100 x 100	60	11.2	1120	1.47
100 x 100	80	8.0	800	1.41
Precast concrete block paving Manufactured to: BS EN 1338:2003 Tensile splitting strength 3.6 Mpa	Abrasion 60mm block Class 3 Abrasion 80mm block Class 4 Resistance to weathering Class 3 Slip/skid resistance Extremely low	Finishes Bush hammered finish	Applications Roads and footpaths on commercial and domestic sites.	

Although every effort is made to ensure consistency of product colour, variations between production batches can occur. Formpave recommend that all products are thoroughly mixed on site by drawing from a minimum of three packs. † Special order * Colour purposes only